

ABSTRACT OF THE DISCLOSURE

A multi-layer circuit board includes first, second, third, fourth, fifth, sixth and seventh insulating substrates; first, second, third, fourth and fifth signal wiring layers; first and second ground wiring layers; and a power wiring layer. Each of the first and seventh insulating substrates has a thickness ranging from 2.5 to 6.5 mil. Each of the second, fourth and sixth insulating substrates has a thickness ranging from 3 to 9 mil. Each of the third and fifth insulating substrates has a thickness ranging from 3 to 23 mil. The first signal wiring layer has a first resistance with respect to the first ground wiring layer. The second signal wiring layer has a second resistance with respect to the first ground wiring layer and the power wiring layer. The third signal wiring layer has a third resistance with respect to the first ground wiring layer and the power wiring layer. The fourth signal wiring layer has a fourth resistance with respect to the second ground wiring layer and the power wiring layer. The fifth signal wiring layer has a fifth resistance with respect to the second ground wiring layer. The first, second, third, fourth and fifth resistances are within the range of 49.5 to 60.5 ohms.

"Express Mail" mailing label number EL6948942J6WS
 Date of Deposit 6 MARCH 81
 I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:
 Assistant Commissioner for Patents, Washington, D.C. 20231.

Bernard Mahan
 (printed name)

B. Mahan
 (signature)